

Highlights

Fast Mobile Broadband for All Your Devices

Share your high-speed mobile broadband connection wirelessly with up to 8 devices.

Security Features

Uses a built-in firewall and industry-standard WPA/WPA2 security protocols to help keep your data safe from prying eyes

Go Anywhere

DWR-930M comes with a 3000mAh* battery give user a longer usage.



DWR-930M

4G/LTE Mobile Router

Features

Connectivity

- Uses a 4G enabled SIM card to connect to the Internet
- Compatible with 802.11n/g/b wireless devices
- Type-C* port for easy charging

Portability

- Connect up to 8 Wi-Fi devices
- Up to 12 hours of battery in one charge so you stay connected longer
- Small size lets you drop it in a purse or pocket and take it wherever you go

Security

- WPA/WPA2 Wi-Fi security protocols for industry-standard encryption
- Built-in firewall helps keep unwanted connections out
- Wi-Fi Protected Setup (WPS) for one-touch setup

The DWR-930M 4G/LTE Mobile Router is a 4G LTE Cat4 high-speed broadband wireless WAN (WWAN) to Wi-Fi mobile hotspot that supports internet speed up to 150Mbps downlink and 50Mbps uplink. The DWR-930M uses a 4G Internet connection to give you an easy-to-set-up Wi-Fi network anywhere you need one. The DWR-930M allows you to create a Wi-Fi hotspot to share your connection with up to 8 Wi-Fi devices. The convenient size means you can share your connection anywhere; use it in a cafe to send e-mail while your friend reads the news, or at the airport so you and your coworkers can work while waiting for your plane.



Connect Anywhere

Simply insert your data-enabled SIM card to set up your very own mobile Wi-Fi network. The DWR-930M is perfect for when you need to quickly set up an impromptu network; it's ideal for business trips when you need to share an Internet connection with everybody during a meeting, or use it for travel, allowing you to provide all your travel companions with Internet access.



High Battery Capacity On The Go

With a powerful 3000mAh battery you can surf the Internet up to 12 hours in one charge.



Technical Specifications

General

| | | |
|--------------------------------|---|---|
| Frequency Support ¹ | <ul style="list-style-type: none"> FDD-LTE: Band 1/3/5/7/8/20/28 TDD-LTE: Band 38/40/41 | <ul style="list-style-type: none"> UMTS/HSDPA/HSUPA: B1/B8 GSM/GPRS/EDGE: B3/B8 |
| Data Throughput ² | <ul style="list-style-type: none"> Downlink up to 150 Mbps | <ul style="list-style-type: none"> Uplink up to 50 Mbps |
| Security | <ul style="list-style-type: none"> WPA/WPA2 PSK Auto (TKIP/AES) | <ul style="list-style-type: none"> WPS Push-Button Connection |
| Advanced Functions | <ul style="list-style-type: none"> Built-in firewall Built-in NAT | <ul style="list-style-type: none"> UPnP |

Physical

| | | |
|-----------------------|--|---|
| Interfaces | <ul style="list-style-type: none"> 802.11n/g/b wireless LAN Nano SIM | <ul style="list-style-type: none"> Type-C port |
| Antenna | <ul style="list-style-type: none"> Internal LTE antenna 1x2 MIMO (UL/DL) | <ul style="list-style-type: none"> Internal Wi-Fi antenna |
| LED | <ul style="list-style-type: none"> Power Status SMS Status Wi-Fi Status | <ul style="list-style-type: none"> Network Type Cellular Signal Strength Battery Indicator |
| Power | <ul style="list-style-type: none"> DC 5 V/1 A ± 5% | <ul style="list-style-type: none"> 3000mAh Poly Li-ion* |
| Dimensions | <ul style="list-style-type: none"> 103 x 63 x 13.35mm | |
| Weight | <ul style="list-style-type: none"> 80g | |
| Operating Temperature | <ul style="list-style-type: none"> 0 to 40 °C (32 to 104 °F) | |
| Storage Temperature | <ul style="list-style-type: none"> -20 to 70 °C (-4 to 158 °F) | |
| Operating Humidity | <ul style="list-style-type: none"> 10% to 90% (non-condensing) | |
| Certifications | <ul style="list-style-type: none"> CE | <ul style="list-style-type: none"> RoHS |

DWR-930M 4G/LTE Mobile Router

| Order Information | |
|-------------------|------------------------|
| Part Number | Description |
| DWR-930M | • 4G/LTE Mobile Router |

1 Supported frequency band is dependent upon regional hardware version.
2 Data rates are theoretical. Data transfer rate depends on network capacity and signal strength.
* Running change
Updated APR 2024