DCS-2802KT Wi-Fi Battery Camera Kit





Product Highlights



High Definition Clarity 1080p Full HD quality video



Motion Detection

Receive motion alert notifications and record video clips



Cloud Recording

Automatically back up video clips to the cloud for access anytime

Smart Home, Made Brilliant

The mydlink™ Pro DCS-2802KT is a bundle consisting of two DCS-2800LH Wi-Fi Battery Cameras and a DCS-H100 Wi-Fi Hub for consumer SOHO surveillance applications. The DCS-2800LH is a compact wireless network battery camera suitable for day-time and night-time outdoor environments. It features built-in night vision, motion detection, and a free mobile app — so you can feel at ease when you're away from home.

Compact Design, Simple Setup

The DCS-2802KT is designed to be compact and unobstrusive, so it can fit in with any decor, indoors or out, no matter where you put it. Setting up the cameras and hub are also a breeze with the free mydlink app. To get started, simply install the app on your mobile device and with a few taps the app will guide you through the entire setup process.

Versatile Feature Set

Despite its small size, the DCS-2802KT has all the features you need for monitoring your home. Onboard Wi-Fi provides extended range and higher bandwidth for smoother 1080p Full HD video streams on any device. The DCS-H100 Wi-Fi Hub together with the mydlink^M app supports two-way audio, simulataneous live viewing, recording, and playback¹ for up to four DCS-2800LH cameras. The Wi-Fi Hub has ports that allow you to record snapshots and video clips to a microSD² card or external HDD, and cloud storage³ is possible with mydlink^M app.

The DCS-2802KT camera's built-in motion detection will automatically send motion alert notifications to your mobile device. Night-time monitoring is possible with the built-in infrared LED that allows for night-time viewing of up to 7.5 meters (25 feet), so you can relax knowing you have 24/7 monitoring of your home or small office. Each camera is powered by two powerful lithium batteries allowing its use for a long period of time without charge.

Access Anywhere Using the Mobile App

With the mydlink[™] app, you have an easy and convenient way for you to look after your family or to monitor your home or office. Stay up-to-date with notifications and check in on those you love at any time. Access your camera using the mydlink[™] mobile app and you can view and manage your camera using your mobile device. You can interact with what you're watching with two-way audio. Enjoy instant control over your home surveillance with the ability to manually trigger video recording, no matter where you are.

Features

- High-quality 1080p Full HD resolution provides detailed snapshots and crisp video
- ♦ 140-degree viewing angle
- ♦ Pinch to Zoom
- Powerful Lithium batteries
- ♦ Built-in IR LEDs to capture video up to 7.5 meters (25 feet) away in complete darkness
- ◆ PIR Motion detection
- ♦ H.264 support for the best video streaming performance
- Receive notifications, and save snapshots and video clips to your mobile device
- View and manage your camera remotely through the mydlink[™] app³
- ◆ Save video clips to a microSD² card, external HDD, or cloud storage⁵
- ♦ Two-way audio
- ♦ AES128-encrypted video and audio streaming



Automated Video Clip Storage Using mydlink™ Cloud Recording

With a mydlink[™] cloud recording subscription, you can have peace of mind with automated storage of your video recordings to a cloud server. Play back recordings in the cloud or download video clips to your mobile device from anywhere, anytime through the Internet. Access real-time live views of your cameras using the mydlink[™] mobile app and set automated schedules via your tablet or mobile phone, no matter where you are.

Product Images DCS-2800LH



Technical Specifications

DCS-2800LH

| Camera | | |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hardware Profile | 1/4" 2 megapixal progressive CMOS sensor Minimum illumination: B/W (Night Mode), IR LEDs on: 0 lux Lens focal length: 1.9 mm Aperture: F2.2 Digital zoom 7.5 m (25 ft) IR illumination distance | Angle of view (16:9): Horizontal: 115° Vertical: 64° Diagonal: 140° Built-in light sensor Built-in microphone |
| Video Compression | H.264 format compression | JPEG for still images |
| Video Resolution | • 1080p (1920 x 1080) • 720p (1280 x 720) | • Up to 24 fps |
| Audio Support | • MPEG-2 AAC LC | • Two-way audio |
| Network | | |
| Connectivity | • 2.4 GHz: 802.11n/g/b wireless with WPA2 encryption | • 922 MHz or 866 MHz for signalling |
| Network Protocols | • RTSP | |
| General | | |
| Buttons | Sync Button | |
| LED | • Status LED | |
| System Integration | | |
| Event Management | PIR motion detectionCloud recordingPush notifications | Manually taken snapshots & video clips are saved to mobile device |



DCS-2802KT Wi-Fi Battery Camera Kit

| Mobile Support | mydlink[™] apps for iPhone, iPad, iPod touch, and Android devices⁴ | |
|--------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| Physical | | |
| Environment | • For Indoor/Outdoor Use | |
| IP Rating | • IP65 | |
| Weight | • 240 grams (8.47 ounces) ± 5% | |
| Battery | • 23.5 Wh, 3.6 V Lithium ion battery | |
| Power Adapter | • Input: 100 to 240 V AC, 50/60 Hz | Output: 5 V DC 2 A (Micro-USB) |
| Power Consumption | Standby state: < 0.22 mW | Active state: < 1,100 mW (Day mode) < 2,500 mW (Night mode) |
| Temperature | • Operating: -20 to 50 °C (-4 to 122 °F) | • Storage: -20 to 70 °C (-4 to 158 °F) |
| Humidity | Operating: 20% to 80% non-condensing | Storage: 5% to 95% non-condensing |
| Certifications | • CE • CE LVD • RCM | • cUL • FCC Class B • ICES |
| Dimensions (HxWxD) | • 85 x 66 x 85 mm (3.37 x 2.6 x 3.37 inches) | |
| Diagram | 65.02 06.48 | 84.45 |



Product Images

DCS-H100

Back View Sync Button Power/Network/Camera LEDs Internal Siren USB 2.0 Port Power Button Power Input

Technical Specifications DCS-H100 Wireless Connectivity • 2.4 GHz: 802.11n/g/b wireless • 2x2 300 Mbps • 922 MHz or 433 MHz for signalling **Network Protocols** • IPv4, ARP, TCP, UDP, ICMP • DNS client • IPv6 • RTSP/SRTP • DHCP Client Security • WPA2 encryption Ports • 1 x 10/100 Base-T LAN port • 1 x USB 2.0 port • 1 x microSD slot Buttons • Reset Button • Sync Button • Power Button LED • Power LED · Camera LED Network LED System Integration mydlink[™] apps for iPhone, iPad, iPod touch, and Mobile Support Android devices⁴



| Physical | | |
|--------------------|-------------------------------------------------|----------------------------------------|
| Environment | For Indoor Use Only | |
| Weight | • 195 grams (6.88 ounces) ± 5% | |
| Power Adapter | • Input: 100 to 240 V AC, 50/60 Hz | Output: 12 V DC 1.5 A |
| Power Consumption | • 18 W maximum | |
| Temperature | • Operating: 0 to 40 °C (32 to 104 °F) | • Storage: -20 to 70 °C (-4 to 158 °F) |
| Humidity | Operating: 20% to 80% non-condensing | Storage: 5% to 95% non-condensing |
| Certifications | • CE • CE LVD • RCM | • ICES • FCC Class B |
| Dimensions (LxWxH) | • 65 x 134 x 150 mm (2.56 x 5.28 x 5.91 inches) | |
| Diagram | 134.00 | 64.05 |
| Order Information | | |
| Part Number | Description | |
| DCS-2802KT | Wi-Fi Battery Camera Kit | |

¹ Use of audio or video equipment for recording the image or audio of a person without their knowledge and consent is prohibited in certain states or jurisdictions. The end-user assumes all liability for compliance with applicable Use of audio or video equipment for recording the image or audio of a person without their knowledge and consent is prohi state, local and federal laws.
 The DCS-H100 is compatible with microSD/SDHC/SDXC cards up to v3.01 and is not compatible with v4.x cards.
 The DCS-2800LH is not supported by the mydlink Home app and is not compatible with D-Link's Connected Home Series.
 Check device app store for OS requirements.
 Subscription required. 1 day of recordings for up to three cameras is free.

Updated 2018/05/15